




GMS2302AL

SOT-23 場效應晶體管(SOT-23 Field Effect Transistors)



**N-Channel Enhancement-Mode MOS FETs**

N 溝道增強型 MOS 場效應管

■ **MAXIMUM RATINGS 最大額定值**

Characteristic 特性參數	Symbol 符號	Rat 額定值	Unit 單位
Drain-Source Voltage 漏極-源極電壓	$BV_{DSS}$	20	V
Gate- Source Voltage 柵極-源極電壓	$V_{GS}$	$\pm 8$	V
Drain Current (continuous) 漏極電流-連續	$I_D$	2.6	A
Drain Current (pulsed) 漏極電流-脈沖	$I_{DM}$	10	A
Total Device Dissipation 總耗散功率 $T_A=25^{\circ}C$ 環境溫度為 $25^{\circ}C$	$P_D$	900	mW
Junction 結溫	$T_J$	150	$^{\circ}C$
Storage Temperature 儲存溫度	$T_{stg}$	-55to+150	$^{\circ}C$

■ **DEVICE MARKING 打標**

GMS2302AL=A2SHB

GMS2302AL

■ELECTRICAL CHARACTERISTICS 電特性

( $T_A=25^{\circ}\text{C}$  unless otherwise noted 如無特殊說明，溫度為  $25^{\circ}\text{C}$ )

Characteristic 特性參數	Symbol 符號	Min 最小值	Typ 典型值	Max 最大值	Unit 單位
Drain-Source Breakdown Voltage 漏極-源極擊穿電壓( $I_D = 250\mu\text{A}, V_{GS}=0\text{V}$ )	$BV_{DSS}$	20	—	—	V
Gate Threshold Voltage 柵極開啓電壓( $I_D = 250\mu\text{A}, V_{GS} = V_{DS}$ )	$V_{GS(th)}$	0.4	—	1.5	V
Diode Forward Voltage Drop 內附二極管正向壓降( $I_S = 0.75\text{A}, V_{GS}=0\text{V}$ )	$V_{SD}$	—	—	1.2	V
Zero Gate Voltage Drain Current 零柵壓漏極電流( $V_{GS}=0\text{V}, V_{DS}= 16\text{V}$ ) ( $V_{GS}=0\text{V}, V_{DS}= 16\text{V}, T_A=55^{\circ}\text{C}$ )	$I_{DSS}$	—	—	1 10	$\mu\text{A}$
Gate Body Leakage 柵極漏電流( $V_{GS}=\pm 8\text{V}, V_{DS}=0\text{V}$ )	$I_{GSS}$	—	—	$\pm 100$	nA
Static Drain-Source On-State Resistance 静态漏源導通電阻( $I_D=2.6\text{A}, V_{GS}=4.5\text{V}$ )	$R_{DS(ON)}$	—	—	85	$\text{m}\Omega$
Static Drain-Source On-State Resistance 静态漏源導通電阻( $I_D=2\text{A}, V_{GS}=2.5\text{V}$ )	$R_{DS(ON)}$	—	—	120	$\text{m}\Omega$
Input Capacitance 輸入電容 ( $V_{GS}=0\text{V}, V_{DS}= 6\text{V}, f=1\text{MHz}$ )	$C_{ISS}$	—	—	480	pF
Common Source Output Capacitance 共源輸出電容( $V_{GS}=0\text{V}, V_{DS}= 6\text{V}, f=1\text{MHz}$ )	$C_{OSS}$	—	—	180	pF
Turn-ON Time 開啓時間 ( $V_{DS}= 6\text{V}, I_D= 1\text{A}, R_{GEN}=6\Omega$ )	$t_{(on)}$	—	—	20	ns
Turn-OFF Time 關斷時間 ( $V_{DS}= 6\text{V}, I_D= 1\text{A}, R_{GEN}=6\Omega$ )	$t_{(off)}$	—	—	65	ns

Pulse Width $\leq 300\mu\text{s}$ ; Duty Cycle $\leq 2.0\%$